Our goal is the sea of stars!

ZHEJIANG ZHEGUI ELECTRIC CO,. LTD.

Address: No.316 Weishiyi Road , Yueqing City,
Zhejiang Province, China
ProvinceTel: 0577-62657695/626577696
Email address:service@giantele.com
Website: www.giant-electric.com

Giantele®

JXF

Distribution box



www.giant-electric.com

ZHEJIANG ZHEGUI ELECTRIC CO., LTD.

JXF

Distribution box

Suitable for circuits with an AC frequency of 50Hz and a rated working voltage below 500V. Under special requirements, the protection level can reach IP55, and there are tapping holes on both the top and bottom of the box. Multiple incoming lines can be reserved with movable opening plates, and the maximum rated current can reach 400A. It is particularly suitable for users of metering control boxes in industrial and mining, hotels, and residential buildings. This product meets the requirements of standards such as GB7251.12-2013 "Low voltage switchgear and control equipment" and IEC60439-2:2011 "Low voltage switchgear and control equipment".



Giantele®

Model meaning

JX	F	□	□	□	/	□	□
①	②	③	④	⑤		⑥	⑦

① Wall mounted control box.
②Indicating protective type.
③Hinge code: 1- represents concealed hinge, 2- represents exposed hinge.
④ Height (cm)
⑤ Width (cm)
⑥ Depth (cm)
⑦ Installation method: M exposed, R concealed, W outdoor.

Normal service conditions

Temperature: -25 ℃~+40 ℃ (under special processes, it can reach -45 ℃);Humidity: ≤ 50% (+40 ℃)
Altitude: The altitude of the installation site shall not exceed 2500m;
Rated working voltage: 230V , 400V
Rated working voltage: 400A
Rated short-circuit breaking capacity: 80kAShell protection level: IP55

Technical parameter

Type	Specifications H×W×D (mm)	Type	Specifications H×W×D (mm)
JXF1–2525/14	250 × 250 × 140	JXF1–6040/23	600 × 400 × 230
JXF1–3025/14	300 × 350 × 140	JXF1–6050/14	600 × 500 × 140
JXF1–3025/18	300 × 350 × 180	JXF1–6050/20	600 × 500 × 200
JXF1–3030/14	300 × 300 × 140	JXF1–6050/23	600 × 500 × 230
JXF1–3030/20	300 × 300 × 200	JXF1–7050/16	700 × 500 × 160
JXF1–4030/14	400 × 300 × 140	JXF1–7050/20	700 × 500 × 200
JXF1–4030/20	400 × 300 × 200	JXF1–7050/25	700 × 500 × 250
JXF1–5040/14	500 × 400 × 140	JXF1–8060/20	800 × 600 × 200
JXF1–5040/20	500 × 400 × 200	JXF1–8060/25	800 × 600 × 250
JXF1–5040/23	500 × 400 × 230	JXF1–10080/20	1000 × 800 × 200
JXF1–6040/14	600 × 400 × 140	JXF1–10080/25	1000 × 800 × 250
JXF1–6040/20	600 × 400 × 200	JXF1–10080/30	1000 × 800 × 300

Notes: customization for special specification and requirement is available